

LT1000 Wheel Loader

基本参数 Technical Parameters

型号 Model	LT1000
操作重量 Operating Weight	36000KG
额定容量 Rated Capacity	10T
铲斗容量 Bucket Capacity	6.5m ³
轴距 Wheelbase	3780mm
最大卸载高度 Max. Dumping Height	3450mm
外形尺寸 Overall Dimensions (L×W×H)	11000x3300x3500mm
转弯半径 Turning Radius	7470mm
最大崛起力 Max. Breakout Force	175kN
最大扭矩 Max. Torque	1350N.m
举升时间 Lifting Time	≤6.5s
液压缸时间 Hydraulic Cylinder Time	≤10.5s
发动机 Engine	Weichai
额定功率 Rated Power	276Kw/2200r/min
轮胎尺寸 Tire Size	29.5-25
传动 Transmission	Beilian ZL80 fixed axle
档位 Gear Shift	Forward 4/Reverse 4



Adopting domestic well-know brand tyres, wear-resistant and reliable, applicable to a variety of harsh working conditions, efficient operation.
采用国内大牌轮胎, 耐磨可靠, 适用多种恶劣工况, 作业高效。



High quality hood materials and design help to absorb and reduce noise generated during loader operation.
高质量的机罩材料和设计有助于吸收和降低装载机工作时产生的噪音。



Multi-functional cab, combined instrumentation real-time display of vehicle operating status, can quickly identify fault information.
多功能驾驶室, 组合仪表实时显示车辆运行状态, 可快速识别故障信息。



Adopting large-displacement double-pump merging hydraulic system, with large cylinder power, fast arm lifting and faster loading speed.
采用大排量双泵合流液压系统, 油缸力量大, 举臂快, 装车速度更快。



Optimise the bucket discharge plate structure, easy to discharge and reduce the impact; the service life is greatly extended.
优化铲斗卸料板结构, 便于卸料, 减少冲击; 使用寿命大幅度延长。



High-power electronically controlled engine with large torque reserve coefficient, strong power and high combustion efficiency.
大功率电控发动机, 扭矩储备系数大, 动力强劲, 燃烧效率高。

