

# LT906 Wheel Loader

## 基本参数 Technical Parameters

型号 Model	LT906
额定载荷Rated Load	600kg
铲斗宽度Bucket Width	1300mm
铲斗容量Bucket Capacity	0.4m <sup>3</sup>
大臂长Arm Length	1830mm
大臂宽Arm Width	290mm
举升高度Lifting Height	3400mm
外形尺寸Overall Dimension	4600x1310x2130mm
操作重量Operating Weight	2060kg
大臂厚Arm Thickness	17mm
最大卸载高度Max. Dumping Height	2400mm
轴距Wheel Base	2100mm
轮距Wheel Tread	1100mm
最小离地间隙Min. Ground Clearance	270mm
中间油缸杆直径Center Cylinder Rod Diameter	35mm
两边油缸杆直径Cylinder Rod Diameter On Both Sides	45mm
发动机Engine	yunnei
额定功率Rated Power	37KW
额定转速Rated Speed	2200 (r/min)
轮胎尺寸Tire Size	8.25-16
变速箱Transmission	265
轴Axles	Isuzu Bridge
车架铰接Frame Articulation	front20mm rear10mm



Cab with broad view, large space and Noise Isolation and vibration absorber meets all kinds of operation.

新型驾驶室拥有宽敞视野, 更大操作空间, 带有噪音隔离和减震功能。

Pilot operated, powershift transmission for easier operation.

先导操作, 动力换挡传动, 操作更轻松。



Articulated thickening treatment, not easy to wear, long service life.

铰接加厚处理, 不易磨损, 使用寿命长。

Anti-slip and wear-resistant tyres for different working conditions

防滑耐磨轮胎, 适用不同工况。

