

# LT910 Wheel Loader

## 基本参数 Technical Parameters

型号 Model	LT910
铲斗容量 Bucket Capacity	0.8m <sup>3</sup>
额定载荷 Rated Load	1000 kg
外形尺寸 Overall Dimension	5600x1810x2750mm
操作重量 Operating Weight	3000 kg
最大卸载高度 Max. Dumping Height	2900 mm
最大卸载距离 Max. Dumping Distance	900 mm
发动机 Engine	Yunnei
气缸数 Cylinder Number	4-cylinders
额定功率 Rated Power	42KW
转向类型 Steering Type	Full-hydraulic, articulated
变矩器类型 Torque Converter Type	Automatic, hydraulic converter
档位 Gear Shift	2 forward, 2 reverse
最大速度 Max. Speed	25 km/h
轴 Axle	Isuzu
轮胎尺寸 Tire Size	20.5-16
行车制动器 Service Brake	Oil drum brake on 4 wheels
驻车制动器 Parking Brake	Hand operated drum brake
操作类型 Operating Type	Mechanical single joystick
可选操作类型 Optional Operating Type	Pilot control
可选配置 Optional Configuration	Air conditioner, rearview camera etc.
可选属具 Optional Attachment	Quick hitch, fork, log grapple etc.



Enhanced hydraulic cylinders for robust operation and powerful lifting effect.

增强型液压油缸，实现稳健运作与强大举升效果。



Large capacity, fast working speed, higher efficiency.

大容量，工作速度快，效率更高。



Articulated thickening treatment, not easy to wear, long service life.

采取增厚工艺，提升耐磨性能，长久耐用。



Simplified operation, real-time monitoring of the overall machine condition, and safety protection.

操作更简易，实时监控整机情况，安全防护。



Thick tire, anti-slip wear, long service life.

专为长效耐磨打造的加厚轮胎，使用寿命增长。



featuring energy-saving and emission-reducing advantages along with powerful performance.

兼具节能减排优势与动力性能。

