



LT925 Wheel Loader

基本参数 Technical Parameters

型号 Model	LT925
额定载荷 Rated Load	2500kg
操作重量 Operating Weight	5400kg
铲斗容量 Bucket Capacity	1.3m ³
最大卸载高度 Max. Dumping Height	3600mm
最大卸载距离 Max. Dumping Distance	1000mm
外形尺寸 Overall Dimension (L×W×H)	6400x2300x2950mm
发动机 Engine	Yuchai
气缸数 Cylinder Number	4
额定功率 Rated Power	85 KW
转向类型 Steering Type	Full-hydraulic, articulated
变矩器类型 Torque Converter Type	Automatic, hydraulic converter
档位 Gear Shift	4 forward, 4 reverse
最大速度 Max. Speed	36 km/h
轴Axe	4WD, heavy hub reduction
轮胎尺寸 Tire Size	16/70-24
轴距 Wheelbase	2700mm
轮距 Wheel Tread	1660mm
行车制动 Service Brake	Gas cap oil disc brake on 4 wheels
驻车制动 Parking Brake	Hand operated caliper disc
操作类型 Operating Type	Mechanical single joystick
可选操作类 Optional Operating Type	Pilot control
可选配置 Optional Configuration	Air conditioner, rearview camera etc.
可选属具 Optional Attachment	Quick hitch, fork, log grapple etc.



Adopting domestic big brand tyres, wear-resistant and reliable, applicable to a variety of harsh working conditions, efficient operation.
采用国内大品牌轮胎，耐磨可靠，适用多种恶劣工况，作业高效。



Dual pump merging system, standard with pilot manoeuvre, easy and flexible to manoeuvre, and high operating efficiency.
双泵合流系统，标配先导操纵，操纵方便灵活，作业效率高。



Stronger power, higher efficiency, electronically controlled high-pressure common rail technology really achieve fuel saving and consumption reduction.
动力更强劲，效率更高，电控高压共轨技术真正达到油耗降耗。



High-precision full LCD reversing camera display instrument, accurately displaying the rear view angle.
高精度全液晶倒车影像显示仪表，准确显示后方视角。



Wing spread hood, large opening hood side door, spacious maintenance space, convenient daily maintenance.
翼展式机罩，大开度机罩侧门，养护空间宽敞，日常维修保养便捷。



Equipped with high wear-resistant blade, which improves the service life of the bucket.
配装高耐磨的刀板，提高了铲斗的使用寿命。

