

LT968 Wheel Loader

基本参数 Technical Parameters

型号 Model	LT968
操作重量 Operating Weight	19500KG
额定容量 Rated Capacity	6000KG
铲斗容量 Bucket Capacity	4m ³
铲斗宽度 Bucket Width	3160mm
轴距 Wheelbase	3100mm
最大卸载高度 Max. Dumping Height	3600mm
最大卸载距离 Max. Dumping Distance	1300mm
外形尺寸 Overall Dimension (L×W×H)	8250X3210X3640mm
转向角 Turning Angle	35°±1°
最大爬坡能力 Max. Climbing Gradient	28°
最小转弯半径 Min. Turning Radius	7134mm
最大掘起力 Max. Breakout Force	175kN
最大扭矩 Max. Torque	1000N.m
举升时间 Lifting Time	≤6.5s
发动机 Engine	Weichai
额定功率 Rated Power	175KW/2200r/min
液压缸时间 Hydraulic Cylinder Time	≤10.5s
轮胎尺寸 Tire Size	26.5-25
前进档 I Forward Gear I	11.5km/h
前进档 II Forward Gear II	38km/h
后退档 I Reserve Gear I	16km/h



Honeycomb type heat dissipation hood, effectively improve heat dissipation performance.
蜂窝型散热器罩, 有效提高散热性能。



Mutiple selection of engine to meet different emission standard.
多种发动机可供选择, 以满足不同的排放标准。



The front and rear frames have a large articulated, heavy-duty design to improve bearing life.
前后车架采用大铰接、重载型设计, 提高轴承使用寿命。



Reinforced drive axles with a safety factor of two times higher and more reliable load-carrying capacity.
加强型驱动桥, 安全系数 2 倍以上, 具有更可靠的承载能力。



Adopting domestic big brand tyres, wear-resistant and reliable, applicable to a variety of harsh working conditions, efficient operation.
采用国内大品牌轮胎, 耐磨可靠, 适用多种恶劣工况, 作业高效。



Multi-functional cab, combined instrumentation real-time display of vehicle operating status, can quickly identify fault information.
多功能驾驶室, 组合仪表实时显示车辆运行状态, 可快速识别故障信息。

