

TMG

BACKHOE LOADER



※The parameters are subject to change without notice

BLT388H



COMPLETELY HAVE THE ALL FUNCTIONS OF MINI TYPE DIGGING MACHINES.



ASCENDANT PERFORMANCE OF COMPLETE APPLIANCE, WITH EXTRAORDINARY OPERATION EFFICIENCY.



LARGE SPACE OPERATION ROOM, STEERING WHEEL DESIGN, MORE CONVENIENT OPERATION.



LARGE BUCKET CAPACITY, REINFORCED BUCKET TEETH AND GUARD PLATE, MORE WEAR-RESISTANT.



Overall dimension

Model	Unit	BLT388H
Length(with bucket on ground)	mm	6650
Overall width (at stabilizer)	mm	2530
Load Bucket width	mm	2400
Height(To the top of the cab)	mm	3120
Height(To the top of the digging pole)	mm	3940
Wheel base	mm	2450
Wheel tread	mm	2139

Loading parameters

Rated load	KG	3000
Operating weight	KG	8600
Rated bucket capacity	m ³	1.5
Dump height	mm	2800
Dump reach	mm	870
Outside of bucket	mm	5750

Digging parameters

Rated digging bucket capacity	m ³	0.3
Max. digging depth	mm	4100
Optional digging depth(telescopic digging boom)	mm	5100
Max. digging radius	mm	5345
Max. dumping height	mm	3740
Max. Digging Height	mm	5470
Lifting force at Max. digging radius	KG	1220

Transmission System

Gearbox type	Synchromesh mechanical shift	
Drive axle type	Water-cooling	
Gear shift position	Front axle/Rear axle	Steering + drive
Size of tire	16.9-28	

Hydraulic system

Working pump discharge	ml/r	63
Working pump pressure	Mpa	20

Oil Capacity

Hydraulic oil tank	L	125
Diesel fuel tank	L	125

Diesel engine

Model	YUCHAI YCD4J22T-125	
Type	Water-cooling	
Optional engine	CUMMINS 4BT3.9-C100	
Rated output	KW	91